

GEOGRIDS DESIGNED TO ENHANCE SOIL STABILISATION AND PAVEMENT PERFORMANCE

GEOFABRICS GEOGRID TRIAXIAL

TECHNICAL DATA SHEET

Geofabrics® Geogrid™ Triaxial is a high performance, multi-axial geogrid engineered for soil stabilisation and ground improvement in road, rail and heavy-duty pavement applications.

Made from a punched polypropylene sheet, it forms a unique hexagonal structure with triangular apertures that confine and interlock with aggregate. This interlocking mechanism creates a Mechanically Stabilised Layer (MSL) that improves load distribution, increases bearing capacity and enhances pavement performance on soft or variable ground conditions.

- Reduces aggregate layer thickness by up to 50% without compromising performance, lowering excavation and fill costs
- Improves bearing capacity and stabilises ballast layers on rail projects, minimising track movement and maintenance requirements
- Increases pavement durability by spreading heavy loads and reducing differential settlement
- All geogrids are manufactured in accordance with a management system which complies with the requirements of ISO 9001:2015

GEOGRID TRIAXIAL - SPECIFICATIONS

PROPERTY	TEST METHOD	UNITS	Triaxial 26	Triaxial 27	Triaxial 29L
Polymer			Polypropylene		
Carbon Black Content	ASTM D1603	%	2		
Minimum Roll Width	-	m	3.95	3.95	3.95
Minimum Roll Length	-	m	50 & 75	50 & 75	50 & 75
Quality Control Strength (MD/CD)					
Typical Unit Weight	EOTA TR41 B.3	kg/m ²	0.25	0.28	0.30
Hexagon Pitch	EOTA TR41 B.4	mm	80 (±4)	80 (±4)	120 (±6)
Radial Secant Stiffness at 0.5% Strain	EOTA TR41 B.1	kN/m	390 (-75)	480 (-90)	540 (-90)
Radial Secant Stiffness Ratio	EOTA TR41 B.1	-	0.8 (-0.15)	0.8 (-0.15)	0.75 (-0.15)
Radial Secant Stiffness at 2% Strain	EOTA TR41 B.1	kN/m	290 (-65)	360 (-65)	400 (-100)
Junction Efficiency	EOTA TR41 B.2	%	100 (-10)	100 (-10)	100 (-10)

The values published are to the best of our knowledge true and correct and are obtained through independent and in-house laboratory testing. The product specification may change at any time without prior notice. No warranty is expressed or implied. Manufactured in a facility certified to the ISO 9001 Quality Management System Standard.

Visit geofabrics.co or call 1300 60 60 20 (AU)
or geofabrics.co.nz or call 0800 60 60 20 (NZ)

GEOFABRICS®
Sustainable solutions

IMPORTANT NOTICE - DISCLAIMER - The information contained in this brochure is general in nature. In particular the content of this brochure does not take account of specific conditions that may be present at your site. For full disclaimer and further information regarding installation visit geofabrics.co/disclaimer © Copyright held by Geofabrics Australasia Pty Ltd. All rights are reserved and no part of this publication may be copied without prior permission. Published July 2026.

